academicJournals

Vol. 17(7), pp. 226-231, 14 February, 2018 DOI: 10.5897/AJB2015.15126 Article Number: FABDF5655923 ISSN 1684-5315 Copyright © 2018 Author(s) retain the copyright of this article http://www.academicjournals.org/AJB

African Journal of Biotechnology

Full Length Research Paper

Characterization of biodiesel obtained from atemoya (Annona squamosa × A. cherimola) seed oil

Luciana Soares Da Cruz¹, Bárbara Lemes Outeiro Araújo², Luiz Roberto Marques Albuquerque¹, Pedro Castro Neto², Angelita Duarte Corrêa¹ and Luciana de Matos Alves Pinto^{1*}

¹Departamento de Química, Universidade Federal de Lavras (UFLA), Campus Universitário, Caixa Postal 3037, CEP 37200-000, Lavras - MG, Brazil.

²Departamento de Engenharia Agrícola, Universidade Federal de Lavras (UFLA), Campus Universitário, Caixa Postal 3037, CEP 37200-000, Lavras - MG, Brazil.

Received 25 November, 2015; Accepted 30 September, 2016

Biodiesel is derived from renewable sources, such as vegetable oils, by means of a transesterification process in which triacylglycerols are transformed into smaller molecules of esters of fatty acids and glycerol. The transesterification reactions of 'Gefner' atemoya (*Annona squamosa × A. cherimola*) seed oil extracted by pressing (physical) and solvent (chemical) processes were studied, with analysis of the methyl esters produced. The reactions were monitored using gas chromatography coupled to mass spectrometry (GC-MS), as well as by hydrogen nuclear magnetic resonance spectroscopy (¹H-NMR). The methyl esters formed during the transesterification reaction with methanol were determined for each oil. The major methyl esters (16:0, 18:0, 18:1 and 18:2) formed during 50 min of reaction were similar to those reported in the literature for other biodiesels; the peak areas and retention times were also similar. No changes in signal intensity over time were observed for the oils obtained by the two extraction methods. It was also noted that the extraction method had no influence on the types of methyl esters formed during biodiesel production.

Key words: Annona, oil extraction, transesterification.

INTRODUCTION

Biodiesel consists of mono-alkyl esters of long-chain fatty acids derived from renewable sources such as vegetable oils, obtained by a transesterification process in which triglycerides are transformed into smaller molecules of fatty acid esters and glycerol. Its use is intended to replace fossil fuels in diesel engines. It has promising potential, not only for its important contribution to reducing environmental pollution, but also for the generation of renewable energy as a replacement for fossil diesel and other petroleum products (Pinto et al., 2005).

In 2013, Brazil was the world's second largest biodiesel

*Corresponding author. E-mail: luca@dqi.ufla.br.

Author(s) agree that this article remains permanently open access under the terms of the <u>Creative Commons Attribution</u> <u>License 4.0 International License</u> consumer, only behind the United States, which had a demand of 5.2 million m^3 . In terms of production, the USA is the global leader, with production of 5.1 million m^3 in 2013, followed by Germany and Brazil, with production of 3.6 and 3.0 million m^3 of biodiesel, respectively (Agência Nacional do Petróleo (ANP), 2013).

In 2004, the Brazilian government launched the National Program for Biodiesel Production (PNPB). Biodiesel can be used to partially or totally replace mineral diesel for light vehicles, trucks, tractors, and generators. In Brazil, the biodiesel mixture has been regulated by law since 2008. At first, the mandatory mixture was 2%, and it has been progressively increased to 5% (Kohlhepp, 2010).

Biodiesel is registered by the United States Environmental Protection Agency as a fuel and as an additive for fuels (Ferrari et al., 2005). After transesterification, biodiesel can be used neat at 100% (B100) or at proportions of 5% upwards in mixtures whose use is intended to replace fossil fuels in diesel cycle engines, without any need for modification of the engine. Various vegetable oils have been successfully tested in transesterifications with methanol or ethanol for the production of biodiesel. The seeds of peanuts, sunflowers, and soybeans, with oil contents of 41.3, 60.2, and 24.5 g 100 g⁻¹, respectively, are widely used for biodiesel production (Constantino et al., 2014). Oils extracted from different fruits have also been explored for biodiesel production (Adekunle et al., 2016; Alexandre et al., 2015), offering non-conventional sources of this biofuel.

Atemoya is an interspecific hybrid of cherimoya (*Annona cherimola*) and sugar-apple (*Annona squamosa*). It was introduced to Brazil in the 1980s and is mainly grown in the south and southeast of the country. In the 1990s, the 'Gefner' hybrid variety was successfully introduced in the northeast of Brazil. The cultivated area now exceeds 1,500 hectares, spread over the States of São Paulo and Paraná, as well as the northeast region (Braga-Sobrinho, 2014).

Atemoya seeds represent around 8.4% of the weight of the fruit and have potential as a source of biodiesel, since the lipid content is 27.3 g 100 g^{-1} (Cruz et al., 2013). This content is close to that of other seeds such as soybeans, which are widely used for biofuel. The use of atemoya seeds to produce biodiesel can add value to the fruit.

The objective of this study was to analyze methyl esters produced during the transesterification reaction of the oil from 'Gefner' atemoya seeds, obtained by physical (pressing) and chemical (solvent) extraction.

MATERIALS AND METHODS

The atemoya was obtained during the 2010/2011 agricultural cycle in an orchard situated in the municipality of Jaíba, in northern Minas Gerais State, Brazil (14°33'-15°28'S, 43°29'-44°06'W, altitude of 500 m). The fruits were harvested at the appropriate stage of maturity and transported overland to Universidade Federal de Lavras. In the laboratory, the fruits were selected considering size, maturity, and absence of defects. Each replicate employed 82 fruits, totaling 902 fruits.

The seeds were separated and washed with distilled water, weighed, and dried in a forced-air circulation oven at 60 to 65°C until they reached humidity lower than 6%. The seeds were then vacuum-packed in plastic bags and stored at around -10°C in a cold chamber until oil extraction (AOAC, 2012).

Oil extractions

Oil extractions were performed by pressing (physical) and solvent (chemical) methods, as described by Cruz et al. (2015). Oil pressing was performed in a continuous expeller press, while chemical extraction employed a Soxhlet extractor with hexane as solvent at 68°C. Humidity determination was performed by dehydration of the oil until constant weight in an oven at 105°C, (Lutz, 2008).

Biodiesel production

Transesterification reactions were performed for 40 min at 50°C in a jacketed reactor, to which 200 ml of vegetable oil and 50 ml of methanol were added. This mixture was heated to a temperature of 50°C under mechanical stirring for 20min. After this time, 6 ml of sodium methoxide (30%) were added, maintaining the temperature and stirring for 40min. The solution was then transferred to a separation funnel for separation of the phases (biodiesel and glycerin) (Silva, 2005). Aliquots were removed at 0, 10, 20, 30, 40, and 50min of reaction. Subsequently, 1ml of each of the six aliquots was treated with 5ml of chloroform, 0.5ml of sulfuric acid, and 10ml of saturated sodium chloride solution. The organic phase obtained was dried with magnesium sulfate, the solvent was removed in a rotary evaporator, and the product was dried with a flow of nitrogen gas. The samples obtained were analyzed using gas chromatography-mass spectrometry (GC-MS), as well as by hydrogen nuclear magnetic resonance spectroscopy (¹H-NMR). For the GC-MS analyses, the samples were resuspended in 0.1 ml of hexane.

Chromatographic analysis

The samples were analyzed using a gas chromatograph coupled to a GC-MS QP2010 Plus mass spectrometer (Shimadzu, Japan) equipped with an AOC-5000 autosampler for liquids and gases (Shimadzu, Japan). A 30 m × 0.25 mm × 0.25 µm RTX-5MS column (5% phenyl to 95% dimethylsiloxane) was used for separation and identification of the compounds. The injector was operated at 220°C in split mode, with a split ratio of 1:20. The carrier gas used was He 5.0, at a flow rate of 1.18 ml min⁻¹. The oven temperature was programmed from 60 to 240°C, with a heating ramp of 5°C min⁻¹, and then from 240 to 270°C, with a heating ramp of 10°C min⁻¹, followed by a final hold at 270°C for 7min. An electron impact mass spectrometer (70 eV) was used in scan mode (45 to 500 Da), with solvent cutting at 3.5min. The detector interface and ion source temperatures were kept at 240°C and 200°C, respectively. The compounds were identified by comparing the mass spectra with library spectra (Wiley 8 and FFNSC 1.2 libraries).

Nuclear magnetic resonance analysis

The ¹H-NMR analyses employed an EFT-60 spectrometer (Anasazi Instruments, Indianapolis, USA), with one-dimensional spectra acquired for the biodiesel samples obtained by both methods.

Methyl esters of fatty acids	Number of carbons from the fatty acid: unsaturation number	Retention time	Reaction time (min)											
			1		10		20		30		40		50	
			Р	С	Р	С	Р	С	Р	С	Р	С	Р	С
Methyl octadecanoate	18:0	24.45	25.46	24.65	19.95	20.74	18.50	21.31	20.95	19.96	22.85	21.86	20.64	23.42
Methyl nonanoate	9:0	26.57	0.09	-	-	-	0.02	-	-	-	-	-	0.04	-
Methyl eicosenoate	20:0	28.10	0.07	8.95	0.08	-	0.12	3.5	3.05	2.83	0.03	-	0.06	-
Methyl hexadecanoate	16:0	28.62	27.39	29.39	21.26	21.49	20.47	22.85	22.72	21.61	24.54	23.85	22.2	24.30
Methyl (9z)-9-octadecenoate	18:1	30.09	41.95	24.31	56.62	29.96	32.89	27.95	29.2	29.82	25.06	26.13	28.69	25.26
Methyl heptadecanoate	17:0	30.53	0.64	1.77	0.66	0.47	0.39	0.64	0.62	0.44	0.87	0.64	0.44	-
Methyl nonadecanoate	19:0	34.16	0.14	0.61	0.14	-	-	-	-	-	0.19	0.14	-	-
Methyl eicosanoate	21:0	35.86	3.25	-	-	2.92	1.76	-	-	-	4.58	3.78	2.96	6.25
Methyl docosanoate	10:0	38.62	0.56	1.64	0.48	0.49	0.25	0.47	0.51	0.48	0.79	0.58	0.51	0.98
Methyl tetracosanoate	24:0	41.04	0.34	0.9	0.31	-	0.16	0.34	0.32	0.31	0.47	0.29	0.3	0.51
Methyl tetradecanoate	14:0	24.45	-	0.49	0.19	-	0.06	0.24	0.19	0.16	0.3	-	-	-
Methyl (9z)-9-hexadecenoate	16:1	28.19	-	1.31	0.3	0.45	0.3	0.94	-	0.36	1.56	0.94	0.5	1.65
Methyl (9z,12z)-9,12- octadecadienoate	18:2	31.86	-	3.73	-	23.08	24.86	21.12	22.04	23	17.72	21.03	22.81	15.32
Methyl (11e)-11-eicosenoate	20:1	35.45	-	1.53	-	-	0.14	-	-	0.44	0.84	0.59	0.42	1.15

Table 1. Methyl esters obtained from transesterification of the seed oil from 'Gefner' atemoya (% peak area), using two oil extraction methods: physical (P) and chemical (C).

Previously treated biodiesel samples (0.1ml) were dissolved in 0.1ml of chloroform deuterated with 99.8% deuterium (CDCl₃), in 5 mm NMR tubes. Tetramethylsilane (0.1 ml) was used as an internal reference standard.

RESULTS AND DISCUSSION

The yield of the transesterification reaction for the oil obtained by pressing of atemoya seeds was 89% methyl esters and 11% glycerin. The biodiesel yield for the chemical extraction was 91% methyl esters and 9% glycerin. These values differed from the results obtained for soybean biodiesel by Ferrari et al. (2005), who reported 57.26% ethyl esters, 22.29% glycerin, 10.04% recovered ethanol, and 10.41% losses. The concentration of glycerin in the biodiesel obtained from atemoya seeds was approximately half that obtained from soybeans, so the concentration of

biodiesel was much higher, and losses were not observed.

Table 1 shows the profile of methyl esters for the transesterification reaction of the oil from 'Gefner' atemoya seeds. The major esters found in the atemoya biodiesel were 16:0, 18:0, 18:1, and 18:2.

The ester area percentages obtained for the physical and chemical extractions, after a reaction time of 50min, at which the biodiesel was decanted, were 22.2 and 24.3 (16:0), 20.64 and 23.42 (18:0), 28.7 and 25.26 (18:1), and 22.81 and 15.32 (18:2), respectively. Comparison of the results obtained here with the findings of Urioste et al. (2008) revealed the presence of one additional ester (18:2).

In chromatographic, determination of the esters of fatty acids was obtained in transesterification reactions of babassu oil with ethanol, propanol, and butanol. Urioste et al. (2008) reported the following areas (%) for ethyl, propyl, and butyl esters, respectively: 24.82, 22.82, and 23.52 (16:0); 21.56, 22.14, and 23.28 (18:0); and 24.60, 22.50, and 24.56 (18:1). It appears that there was virtually no difference between the areas of the three ethyl, propyl and butyl esters formed in babassu biodiesel.

In their study with soybean oil, Ferrari et al. (2005) observed the following areas (%) for ethyl esters of fatty acids: 11.29 (16:0), 3.54 (18:0), 22.45 (18:1), 54.62(18:2), and 8.11 (18:3), with a predominance of unsaturated fatty acids. These esters were the same as those obtained in the transesterification of atemoya seed oil, with the exception of the 18:3 ester, which was not found in atemoya oil. The 18:2 methyl ester of the atemoya seed oil extracted by the pressing and solvent methods showed areas of 22.81% and




Figure 1.¹H-NMR spectrum of methyl esters obtained in the transesterification of the 'Gefner' atemoya seed oil extracted physically (by pressing), at 50 min reaction time.

15.32%, respectively, which were smaller than the value obtained for soybean oil. On the other hand, the 18:0 and 18:1 esters of atemoya oil had greater areas, compared to the soybean oil, with values of 20.64% (pressed) and 23.42% (solvent extracted), and 28.69% (pressed) and 25.26% (solvent extracted), respectively. These data show that the predominant esters in current biodiesels are 16:0, 18:0, 18:1, 18:2, and 18:3.

Marques et al. (2010) emphasized the importance of considering instrumental precision when evaluating major peak areas, in order to increase the accuracy of determination of esters of fatty acids formed during transesterification reactions. Barbosa et al. (2010) reported the following areas (%) for ethyl esters of soybean seed oil: 16.0 (16:0), 2.4 (18:0), 23.5 (18:1), and 51.2 (18:2). In the present work, greater areas were obtained for 16:0, 18:0, and 18:1 esters in the atemoya oil biodiesel obtained using both forms of oil extraction (press and solvent), while the value obtained for the 18:2 ester was smaller. Benito et al. (2014) studied the biodiesel potential of Annona diversifolia seed oil and reported the following areas (%) for methyl esters: 16.4 (16:0), 5.22 (18:0), 70.4 (18:1), and 7.97 (18:2). The areas obtained for the 16:0, 18:0, and 18:2 methyl esters were greater for the decanted biodiesel from atemoya oil extracted by both techniques (physical and chemical), while the area was smaller for the 18:1 ester.

Methanol is the main alcohol used in transesterification in many countries (Pinto et al., 2005). In Brazil, several research groups and small producers use the methyl pathway for the production of biodiesel, because methanol is more reactive, while ethanol causes greater dispersion of glycerin in the biodiesel, making separation difficult (Lôbo et al., 2009). A reaction time of 30min was required for the formation of methyl esters in the biodiesel, similar to the duration of 25min reported by Urioste et al. (2008) for biodiesel from Babassu, where the major esters formed were 16:0, 18:0, and 18:1.

(2002)Encinar et al. observed that the transesterification reaction was very fast, with conversion into ethyl esters close to the maximum value after only 5 to 10min of reaction, and stabilization at a maximum value after 20 to 30min. These values were similar to those found for the formation of biodiesel from atemoya oil, which occurred after 20 to 30min of reaction. However, in the study of Ferrari et al. (2005), chromatographic monitoring of the products formed after various reaction times showed that a time of 5min was sufficient for the conversion of neutral and dried oil into ester. The conversion of fatty acids into methyl esters in the atemoya oil occurred between 5 and 10min of reaction, stabilizing at a maximum value after 20 to 30min. The physical extraction (pressing) of atemoya seed oil is economically advantageous and provides a high oil extraction efficiency of 88.9g 100 g⁻¹ (dry mass basis) (Cruz et al., 2015).

Furthermore, in comparison with chemical extraction using solvent, a disadvantage of the latter has greater oxidation of the extracted oil. The profile of the methyl esters identified by GC-MS was confirmed by ¹H-NMR. Figures 1 and 2 show the major chemical shifts characterizing the esters, formed after 50 min of reaction. No changes in signal strength or in the hydrogen chemical shifts with time were observed after the




Figure 2. ¹H-NMR spectrum of methyl esters obtained in the transesterification of the 'Gefner' atemoya seed oil extracted chemically (using solvent), at 50 min reaction time.

Table 2. Chemical shifts (ppm) obtained by	¹ H-NMR (60 MHz) of
biodiesel in CDCl ₃ at 25°C (physical extraction).

н	δ _H						
п	Atemoya biodiesel	Paiva et al. (2010)					
CH₃	0.89	0.90					
CH ₂	1.27	1.2 – 2.5					
CH ₂ (α-carbonyl)	2.40	2.1 – 2.5					
CH₃-O	3.68	3.5 – 4.8					
CH ₂ (vinylic)	5.99	4.5 – 7.0					

Table 3. Chemical shifts (ppm) obtained by 1 H-NMR (60 MHz) of biodiesel in CDCl₃ at 25°C (chemical extraction).

н	δ _Η						
п	Atemoya biodiesel	Paiva et al. (2010)					
CH₃	0.89	0.90					
CH ₂	1.27	1.2 – 2.5					
CH ₂ (α-carbonyl)	2.40	2.1 – 2.5					
CH ₃ -O	3.68	3.5 – 4.8					
CH ₂ (vinylic)	5.99	4.5 – 7.0					

transesterification reactions of the atemoya oils obtained by the two extraction methods (physical and chemical). This suggests that the extraction method had no influence on the characteristics of the oil obtained, or, therefore, on the product (biodiesel). Tables 2 and 3 show the ¹H-NMR data (60 MHz) for the biodiesel (in CDCl₃), compared with the literature. There was a good correlation of the chemical shifts in the spectra with the data reported by Paiva et al. (2010).

Conclusions

The methyl esters formed from the 16:0, 18:0, 18:1, and 18:2 fatty acids during the transesterification reaction were similar to those present in other current biodiesels.

The method used for oil extraction had no influence on the types of methyl esters formed during biodiesel production.

The oil from atemoya seeds has potential for use as biodiesel, with advantages including addition of value to the fruit and a use for unwanted biomass (the seeds) that might otherwise be treated as waste.

CONFLICT OF INTERESTS

The authors have not declared any conflict of interests.

ACKNOWLEDGMENTS

The authors would like to thank CAPES and FAPEMIG

for financial support, and the Center for Analysis and Chemical Prospecting (CAPQ) at the Chemistry Department of UFLA for the use of equipment.

REFERENCES

- Adekunle AS, Oyekunle JAO, Obisesan OR, Ojo OS, Ojo OS (2016). Effects of degumming on biodiesel properties of some nonconventional seedoils. Energy Rep. 2:188-193.
- Agência Nacional do Petróleo (ANP)(2013). Brazilian National Agency of Petroleum, Natural Gas and Biofuels – ANP. Gás Natural e Biocombustíveis. Resolução nº 30. Biocombustíveis. Available at: <http://anp.gov.br/?pg=60467&m=&t1=&t2=&t3=&t4=&ar=&ps=&cach ebust=1412632 744151>. Accessed: March 3rd, 2015.
- Alexandre ACF, Silveira EV, Castro CFS, Sales JF, Oliveira LCS, Viana LH, Barbosa LCA (2015). Synthesis, characterization and study of the thermal behavior of methylic and ethylic biodiesel produced from tucumã (Astrocaryum huaimi Mat.) seed oil. Fuel 161:233-238.
- Association of Official Analytical Chemistry (AOAC) (2012). Official Methods of Analysis. 19th ed. Gaithersburg, 3000p. Barbosa CD, Serra TM, Meneghetti SMP, Meneghetti MR (2010).
- Barbosa CD, Serra TM, Meneghetti SMP, Meneghetti MR (2010). Biodiesel production by ethanolysis of mixed castor and soybean oils. Fuel 89:3791-3794.
- Benito RT, Ramírez DG, Prada HZ, Sánchez JAC, Lino Reyes L, Chumacero AR, Salazar JAR (2014). *Annona diversifolia* seed oil as a promising non-edible feedstock for biodiesel production. Ind. Crops Prod. 52:400-404.
- Braga-Sobrinho R (2014). Integrated production of *Annonaceae* in Brazil. Rev. Bras. Fruticult. 36(SPE1):102-107.
- Constantino AF, Lacerda JRV, Santos RB, Greco SJ, Silva RC, Neto AC, Barbosa LL, Castro EVR, Freitas JCC (2014). Análise do teor e da qualidade dos lipídeos presentes em sementes de oleaginosas por RMN de baixo campo. Quím. Nova 37(1):10-17.
- Cruz LS, Corrêa AD, Bastos VA, Neto PC, Pinto LMA (2015). Chemical and physicochemical characterization of the seed oil from 'Gefner' atemoya. Afr. J. Biotechnol. 14(2):143-148.

- Cruz LS, Lima RZ, Abreu CMP, Corrêa AD, Pinto LMA (2013). Physical and chemical characterization of fractions of fruit atemoya Gefner. Ciênc. Rural 43(12):2280-2284.
- Encinar JM, González JF, Rodríguez JJ, Tejedor A (2002). Biodiesel fuels from vegetables oils: transesterification of *Cynara cardunculus* L. oils with ethanol. Energ. Fuels 19:443-450.
- Ferrari RA, Oliveira VS, Scabio A (2005). Biodiesel de soja: taxa de conversão em ésteres etílicos, caracterização físico-química e consumo em gerador de energia. Quím. Nova 28(1):19-23.
- Kohlhepp G (2010). Análise da situação da produção de etanol e biodiesel no Brasil. Estud. Av. 24(68):223-253.
- Lôbo IP, Ferreira SLC, Cruz RS (2009). Biodiesel: Parâmetros de qualidade e métodos analíticos. Quím. Nova 32(6):1596-1608.
- Lutz IA (2008). Métodos químicos e físicos para análise de alimentos. 4th edition. IMESP, São Paulo. 1020p.
- Marques MV, Naciuk FF, Mello MAS, Seibel NM, Fontoura LAM (2010). Determinação do teor de ésteres graxos em biodiesel metílico de soja por cromatografia gasosa utilizando oleato de etila como padrão interno. Quím. Nova 33(4):978-980.
- Paiva DL, Lampman GM, Kriz GS, Vyvyan JRS (2010). Introdução à Espectroscopia. 4th edition. Cengage Learning, São Paulo. pp.150-152.
- Pinto AC, Guarieiro LLN, Rezende MJC, Ribeiro NM, Torres EA, Lopes WA, Pereira PAP, Andrade JB (2005). Biodiesel, an overview. J. Braz. Chem. Soc. 16:1313-1330.
- Silva CLM (2005). Obtenção de ésteres etílicos a partir da transesterificação do óleo de andiroba com etanol. Dissertation. Universidade Estadual de Campinas, Instituto de Química, Campinas, SP. 64p.
- Urioste D, Castro MBA, Biaggio FC, de Castro HF (2008). Síntese de padrões cromatográficos e estabelecimento de método para dosagem da composição de ésteres de ácidos graxos presentes no biodiesel a partir do óleo do babaçu. Quím. Nova 31(2):407-412.